



Germanischer Lloyd

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 54 566 - 07 HH

Company Ryco Hydraulics Pty. Ltd.
19 Whitehall Street
Footscray, VIC 3011, AUSTRALIA

Product Description High pressure hoses - Flame resistant

Type Avenger T2A, Diehard T2D, TXA2D, Slider T2S, Survivor RQ2

Environmental Category None

Technical Data / TECHNICAL DATA

Range of Application	Hose design:	Synthetic rubber tube, two steel wire braid, synthetic rubber cover acc. to EN 853 - 2SN, SAE 100R2AT				
	Hose Type:	T2A	T2D	TXA2D	T2S	RQ2
	Size range (DN):	6 to 32	6 to 32	12 to 32	6 to 25	6 to 50
	Pressure range (bar):	420 to 125		375 to 175	420 to 167	400 to 90
	Ferrules / Nipples:	T200, T700 Series Non-Skive				
	Temperature range:	- 40 [°C] to 100 [°C]				

RANGE OF APPLICATION

The above mentioned hose types are type approved for the use in:
Fuel oil-, Lubricating oil-, Hydraulic oil-, Bilge-, Ballast-, Freshwater cooling-,
Sea water cooling-, Compressed air- and Ancillary piping systems.

The selection of the hoses for the corresponding application is to be in accordance with the instructions of the hose manufacturer.

Test Standard Regulations for the Performance of Type Tests, Part 6-Test Requirements for Mechanical Components and Equipment: 1998, EN 853:1996.

Documents - Test reports of product tests according EN 853:1996, Fire test reports according to ISO 15540/15541:1999, Burst test reports on hose assemblies
- Ryco hydraulics catalogue RHY-PRO206AUS

Remarks Refer to page 2

Valid until 2012-11-27

Page 1 of 2

Type Approval Symbol



File No. II.D.01

Hamburg, 2007-11-28

Germanischer Lloyd

i. V. Hansp. Raschle *Hagen Markus*
Hanspeter Raschle Hagen Markus