



Germanischer Lloyd

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 54 573 - 07 HH

Company Ryco Hydraulics Pty. Ltd.
19 Whitehall Street
Footscray, VIC 3011, AUSTRALIA

Product Description Low pressure hoses - Flame resistant

Type Textile M2

Environmental Category None

Technical Data / TECHNICAL DATA

Range of Application Hose design: Synthetic rubber tube, two textile braids, synthetic rubber cover acc. to SAE J517 - 100R3
Size range: DN 6 to 20
Pressure range: 86 to 52 bar
Ferrules / Nipples T400 (Non-Skive) acc. to Ryco catalogue
Temperature range: - 40 [°C] to 100 [°C]
Fire sleeve: FS1072

RANGE OF APPLICATION

The hose type M2R provided with a fire sleeve of type FS1072 is type approved for the use in fuel oil-, lubricating oil-, hydraulic oil-, bilge-, ballast-, sea water cooling and compressed air piping systems.

Without fire sleeve this hose type is approved for the use in fresh cooling and ancillary piping systems containing non-flammable liquids.

Test Standard Regulations for the Performance of Type Tests, Part 6-Test Requirements for Mechanical Components and Equipment: 1998, SAE J517:2001.

Documents - Test reports of product tests according SAE J517:2001, Fire test reports according to ISO 15540/15541:1999, Burst test reports on hose assemblies
- Ryco hydraulics catalogue RHY-PRO206AUS

Remarks Refer to page 2

Valid until 2012-11-27

Page 1 of 2

Type Approval Symbol



File No. II.D.02

Hamburg, 2007-11-28

Hanspeter Raschle

Hanspeter Raschle

Hagen Markus

Hagen Markus

Germanischer Lloyd